

MEDARIS-Neovo MRX-15W

15" High Quality Medical Display with Anti-Glare Hard Glass Front



- ▶ Endoscopy optimized Real-time Image Display without Time Lag
- ▶ Cleanser resistant full flat Glass and Aluminum Surface
- ▶ all purpose - five different PC and Video Signal Inputs
- ▶ user friendly - Picture in/and Picture Hotkeys
- ▶ mountable on VESA 100



Hygiene + Patient Environment

The MRX-15W Display is equipped with an additional Ground Pin and a Medical Power Supply, which fulfills the EN60601-1 3rd. Edition and it is also tested according to the EN60601-1-2. The MRX-15W is also easy to clean because of the closed Housing and full flat Hard Glass front.

Introducing MEDARIS-Neovo MRX-15W, Werth Systems powerful new addition to the field monitor range. Featuring a crystal clear TFT panel, things seem even better for the user with an eye for quality. In addition to the Top Level Imageality, the MRX-15W also has a Flicker Free Backlight for a stress free, long time working. The new TFT Panel and Signal Input Board has a very high Color fidelity especially for professional Environments and realistic colors. It has different Analog and Digital Signal Inputs for nearly every Device.

Technical Data MEDARIS-Neovo MRX-15W

Description	MRX-15X
Part Number	2000574
Displaysize	38.1cm (15')
Paneltype	TFT Panel
Light Reflection Rate / Coating	1% / Anti-reflective & Scratch-resistant coating
Backlight	CCFL
Optimal Resolution	1024x768 @60Hz
Screen Format	5:4
Contrast Ratio	3000:1
Brightness	320 cd/m2
Response Time	4 ms (grey to grey)
Viewing Angle	170°(H) / 160°(V)
Panel Color Depth	Real 8 Bit
Color Bandwith	16.7M / NTSC 101,4% (CIE1976) / sRGB 122,7%
Image Enhancer	Advanced Image Platform - for real Colors and Greyscale
Signal Input	1xVGA, 1xDVI-D (HDCP), 1xCVBS (RCA), 1xS-Video,
Signal Output	none
Housing	closed Aluminum Case with NEOV Optical Glass -Hardness 9H
Color	White
Mounting	VESA 100
Tilt	0° / +20°
Height Adjustment	optional
Swivel	No
Pivot	optional
Power Supply	external, medical 65W Power Supply 12V DC, 110-240V AC Input
Power Consumption	36W typical
Additional Ground Pin	Yes, according to DIN 42801
Dimensions (with Stand)	380x359x155mm (WxHxD)
Weight	4.8 Kg
Temperature Range	0°C to 40°C
Production Control	ISO 9001
Warranty	3 Years pick up and return
Norms / Standards	CE, RoHS, EN60601-1-2:2007/AC2010, Power Supply: EN60601-1:2006/A1:2013
Mode of Operation	Continuous Operation
Life Expectancy	MTBF: 50000h
Scope of Delivery	Manual, Power Supply, AC-Cord 1.5m, 1xVGA Cable, 1xDVI Cable, 1xCVBS Cable



Options for the MEDARIS-Neovo MRX-15W


Additional Warranty:

Warranty Extension to 3Years / 4Years / 5Years Warranty - pick up and return or 48h replacement in advance

Mounting Devices and Stands



Part No. 2000398



Part No. 2000491



Part No. 2000492



Part No. 2000490



Part No. 2000494